










**Pompy membranowe BX / BX double diaphragm pumps technical data**

Model	 <a href="#">BX 50</a>	 <a href="#">BX 80</a>	 <a href="#">BX 81</a>	 <a href="#">BX 100</a>	 <a href="#">BX 150</a>	 <a href="#">BX 250</a>	 <a href="#">BX 251</a>	 <a href="#">BX 502</a>	 <a href="#">BX 503</a>
<b>Przylącze ssania</b>	G ½	G 1	G 1	G 1	G 1 ¼	G 1 ½	G 1 ½	G 2	G 3
<b>Przylącze powietrza.</b>	G½	G ½	G ½	G ½	G ½	G ½	G ½	G ½	G ½
<b>Maks. Wysokość ssania - m</b>	5	5	6	5	5	5	6	4	5
<b>Maks. przepływ - l/min</b>	50	90	100	150	220	340	340	650	850
<b>Maks. Wys podnożenia w - m</b>	70	70	70	70	70	70	70	70	70
<b>Maks ciśnienie zasilania pow.</b>	7	7	7	7	7	7	7	7	7
<b>Maksymalna średnica części stałych - mm</b>	3	4	4	4	5	6	6	8	10
<b>Waga PP - kg</b>	3,6	5,5	---	7,5	12	16	---	54	56
<b>ECTFE - kg</b>	4,2	7	---	9	14	20	---	---	---
<b>Al - kg</b>	4,2	---	6,5	---	16	---	21	---	---
<b>AISI 316 - kg</b>	6,5	10,5	---	---	21	---	32	---	---
<b>PVDF</b>	---	---	---	---	---	---	---	65	67
<b>Dostępny Materiał korpusu</b>	PP ECTFE E Al Aisi 316	PP ECTFE Aisi 316	Al	PP ECTFE	PP ECTFE Al Aisi 316	PP ECTFE	Al Aisi 316	PP PVDF	PP PVDF

